

신뢰기반 디지털 ID 관리기술

한국과학기술정보연구원 조진용

jiny92@kisti.re.kr

Audience

대상

- ¶ 통합인증과 인증연합에 관심 있는 누구나
- ¶ 인증연합에 참여 중인 학연 기관 및 서비스제공자

수준

- ¶ 초급+α
- ¶ IT 관련 기초지식 필요

참고

- ¶ CentOS 7 기준

Agenda

1교시 (13:30PM - 14:45PM)

- ¶ 실습환경 구성
- ¶ SAML 표준 소개
- ¶ 아이디제공자의 구축
- ¶ 실습

2교시 (15:00PM - 16:30PM)

- ¶ MFA의 이해
- ¶ 실습

실습환경 구성

목적

- ¶ SAML의 개념과 동작원리 이해
- ¶ 아이디제공자(Identity provider)의 관리운영

할일

- ① 계정 생성
- ② Chrome용 SAML 플러그인 설치
- ③ notepad++ 설치

실습자료

<https://edu.kafe.or.kr>

실습환경 구성 - 계정 생성

계정 생성이 필요하지 않음 (Home 계정)

¶ KAFE 참여기관(https://www.kafe.or.kr/participants_idp)

계정 생성이 필요 (Guest 계정)

- ① <https://coreen-idp.kreonet.net> 방문
- ② 사용자 등록 메뉴에서 계정 생성
 - * 본명 사용
 - * 연구기관이나 교육기관 구성원은 기관 이메일 주소 입력

기억하세요!

¶ Guest 계정의 이름은 'COREEN Set.ID by KAFE'




실습환경 구성 - Chrome용 SAML Plugin

설치 방법 (Chrome 브라우저)

- ① <https://chrome.google.com/webstore/category/extensions> 또는 Google에서 'Chrome 확장프로그램 설치'로 검색
- ② 'SAML' 로 검색
- ③ 'SAML DevTools extension' 로 설치

설치 확인

¶ Chrome 브라우저에서 F12 키 입력(시크릿 창x)



실습환경 구성 - Notepad++

설치 방법

- ① Google에서 'notepad++'로 검색
- ② 최신버전을 다운로드 받아 설치



Current Version 8.4.2

- Home
- Download**
- News
- Online Help
- Resources
- RSS
- Donate
- Author


Downloads

- Download Notepad++ v8.4.2
- Download Notepad++ v8.4.1
- Notepad++ 8.4 (Stand up for Ukraine)
- Notepad++ 8.3.3 (Make Apps, not war)
- Notepad++ 8.3.2 (Declare variables, not war)
- Notepad++ 8.3.1 (Boycott Beijing 2022)

Part I . SAML



Authentication & Authorisation



Identity Management

Digital Identity Model

개인정보 관리주체:

서비스제공자

Centralized Identity

Register once, trusted by one

Service provider establishes and maintains users' identity and related data in its system



사용자 소속기관

Federated Identity

Register once, trusted by many

Service provider trusts identities established and maintained by other identity providers



개인

Decentralized Identity

Register once, trusted globally

Users have a self-managed digital identity independent of individual service providers



Cost, Portability, Security

Img Source: IoTex

Centralized/Federated Model

Examples

Sign in with

OR

Register now | Forgotten?

Federated

Centralized

Year	Company	Impact
2018	Blank Media	7.6 million compromised accounts
2018	Quora	100 million compromised accounts
2018	Facebook	50 million compromised accounts
2018	Cathay Pacific	9.4 million compromised accounts, including 860 thousand passport numbers
2018	Marriot	500 million compromised accounts
2017	Equifax	143 million accounts exposed, including 209k credit card numbers
2016	Uber	57 million compromised accounts
2016	MySpace	360 million compromised accounts
2016	Linkedin	117 million emails and passwords leaked
2015	Anthem Inc	80 million company records were hacked, including social security numbers
2014	ebay	145 million compromised accounts
2013	Target	110 million compromised accounts
2013	Yahoo	All 3 billion accounts compromised

Can trust?

Trust Framework

What Is A Trust Framework?

Trust Frameworks provide a common set of agreed upon standards for disparate entities to establish trust. Ensuring all organizations meet the same agreements and requirements allows for forgoing additional legal contracts or peer-to-peer agreements. This is often referred to as "scalable" trust, because each new connection between organizations and their users/clients grows the network

of exchange participants at an exponential, rather than linear, rate. In the case of digital identity in online transactions, the Trust Framework provides policy and technical interoperability for the issuers of digital identity credentials, the individuals asserting their identities, and the organizations relying on the identity assertions linked to the digital credentials.



A common set of agreed upon standards and policies for disparate entities to establish trust
: 이질적인 개체들이 동의한 표준기술과 정책의 집합

Source: DirectTrust, <https://directtrust.org/identity>

Key Enabler of Federated Models

Standards

Universities & Research Institutions

Enterprise

	SAML 2.0	OAuth2	OpenID Connect
What is it?	Open standard for authorization and authentication	Open standard for authorization	Open standard for authentication
History	Developed by OASIS in 2001	Developed by Twitter and Google in 2006	Developed by the OpenID Foundation in 2014
Primary use case	SSO for enterprise apps	API authorization	SSO for consumer apps
Format	XML	JSON	JSON

Complicated
however, well-gardened ecosystem

- Metadata management
- Samesite problem
- Signature verification
- Limited support of non-web applications

Simple!

- Almost all OSS R&S platforms

SAML이란?

SAML [샘엘]

Security Assertion Markup Language
웹 통합인증(Single sign-on)을 위한 국제표준

보안 주장 표시 언어?



Security Assertion Markup Language (SAML) V2.0 Technical Overview

Committee Draft 02

25 March 2008

Specification URIs:

This Version:

<http://docs.oasis-open.org/security/saml/Post2.0/sstc-saml-tech-overview-2.0-cd-02.html>

<http://docs.oasis-open.org/security/saml/Post2.0/sstc-saml-tech-overview-2.0-cd-02.pdf>

<http://docs.oasis-open.org/security/saml/Post2.0/sstc-saml-tech-overview-2.0-cd-02.odt>

Previous Version:

N/A

Latest Version:

<http://docs.oasis-open.org/security/saml/Post2.0/sstc-saml-tech-overview-2.0.html>

<http://docs.oasis-open.org/security/saml/Post2.0/sstc-saml-tech-overview-2.0.pdf>

<http://docs.oasis-open.org/security/saml/Post2.0/sstc-saml-tech-overview-2.0.odt>

Technical Committee:

OASIS Security Services TC

Chairs:

Hal Lockhart, BEA

Brian Campbell, Ping Identity

Editors:

Nick Ragouzis, Enosis Group LLC

John Hughes, PA Consulting

Rob Philpott, EMC Corporation

Eve Maler, Sun Microsystems

Paul Madsen, NTT

Tom Scavo, NCSA/University of Illinois

Related Work:

N/A

Abstract:

The Security Assertion Markup Language (SAML) standard defines a framework for exchanging

SAML

웹 통합인증(싱글사인온)을 위한 XML 규약

SAML 1.1(`03), SAML2.0(`05, Errata(정오표)/`19)

¶ OASIS 보안서비스 기술위원회 제정

연구교육분야 활용(`05~)

¶ SWITCH(스위스 연구망)

강화된 보안 vs 적용 어려움


웹 환경 지원(모바일 미지원)

¶ OpenID Connect(OIDC) 출현


통합인증(싱글사인온, SSO)

하나의 아이디와 한번의 로그인으로 다수 응용서비스 이용

- ㉮ 보안성 ↑
- ㉮ 편의성 ↑
- ㉮ 관리비용 ↓



통합인증이 없는 경우



통합인증이 있는 경우

SAML 통합인증 시스템의 구성

아이디(신원정보) 제공자/Identity provider(IdP)

¶ 신원정보 관리

¶ 사용자 인증(로그인)

¶ SAML 메시지 처리(서명 등)

서비스 제공자/Service provider(SP)


¶ 사용자 인가(권한부여)

¶ SAML 메시지 처리(서명검증 등)

특징


¶ IdP와 SP가 분리되어 있음

¶ 일반적으로 HTTP를 전송규약으로 이용




How SAML Work

Example: WebSSO Profile on Full Mesh Architecture



(1) 메타데이터 교환



(2) 인증메시지 교환

Source: Wikipedia, ECLIPSE Foundation

SAML Metadata

아이디제공자/서비스제공자의 시스템 정보를 저장한 XML 파일

내용

¶ 개체식별자(EntityID)

¶ 기관도메인(Scope)

¶ 암호키(서명/암호화)

¶ 서비스 주소

* Protocol endpoints

¶ 부가정보

```
<?xml version="1.0"?>
<md:EntityDescriptor xmlns:md="urn:oasis:names:tc:SAML:2.0:metadata" xmlns:shibmd="urn:mace:shibboleth:metadata:1.0" xmlns:ds="http://www.w3.org/2000/09/xmldsig#"
  EntityID="https://coreen-idp.kreonet.net/idp/simplesamlphp" ID="pfx7e712720-a30c-d1f4-0548-88fe79206281"><ds:Signature>
  <ds:SignedInfo><ds:CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#"/>
  <ds:SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1"/>
  <ds:Reference URI="#pfx7e712720-a30c-d1f4-0548-88fe79206281"><ds:Transform Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-signature"/><ds:
  <ds:KeyInfo><ds:X509Data><ds:X509Certificate>MIIDuTCCAqGgAwIBAgIJAOcu00jK2GcAMA0GCSqGSIb3DQEBCwUAAQ8tCzAJBgNVBAYTAkRlZGVVQVQKDAVLSVNUST
  <md:IDPSSODescriptor protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:protocol">
  <md:Extensions>
  <shibmd:Scope xmlns:shibmd="urn:mace:shibboleth:metadata:1.0" regexp="false">coreen.or.kr</shibmd:Scope>
  </md:Extensions>
  <md:KeyDescriptor use="signing">
  <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
  <ds:X509Data>
  <ds:X509Certificate>MIIDuTCCAqGgAwIBAgIJAOcu00jK2GcAMA0GCSqGSIb3DQEBCwUAAQ8tCzAJBgNVBAYTAkRlZGVVQVQKDAVLSVNUST
  </ds:X509Data>
  </ds:KeyInfo>
  </md:KeyDescriptor>
  <md:KeyDescriptor use="encryption">
  <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
  <ds:X509Data>
  <ds:X509Certificate>MIIDuTCCAqGgAwIBAgIJAOcu00jK2GcAMA0GCSqGSIb3DQEBCwUAAQ8tCzAJBgNVBAYTAkRlZGVVQVQKDAVLSVNUST
  </ds:X509Data>
  </ds:KeyInfo>
  </md:KeyDescriptor>
  <md:ServiceEndpoint>
  <md:SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Redirect" Location="https://coreen-idp.kreonet.net/simplesaml/saml2/idp/SingleLogout
  <md:SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST" Location="https://coreen-idp.kreonet.net/simplesaml/saml2/idp/SingleLogoutServ
  <md:NameIDFormat>urn:oasis:names:tc:SAML:2.0:nameid-format:transient</md:NameIDFormat>
  <md:SingleSignOnService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Redirect" Location="https://coreen-idp.kreonet.net/simplesaml/saml2/idp/SSOService.p
  <md:SingleSignOnService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST" Location="https://coreen-idp.kreonet.net/simplesaml/saml2/idp/SSOService.php"/
  <md:IDPSSODescriptor>
  <md:Organization>
  <md:OrganizationName xml:lang="en">KREONET</md:OrganizationName>
  <md:OrganizationDisplayName xml:lang="en">KREONET</md:OrganizationDisplayName>
  <md:OrganizationURL xml:lang="en">http://www.kreonet.net/</md:OrganizationURL>
  </md:Organization>
  <md:ContactPerson contactType="technical">
  <md:GivenName>coreen</md:GivenName>
  <md:SurName>support</md:SurName>
  <md:EmailAddress>coreen@kreonet.net</md:EmailAddress>
  </md:ContactPerson>
  </md:EntityDescriptor>
```

SAML Request

서비스제공자가 전송하는 인증요청 메시지

메시지 내용

¶ SSO 서비스 주소

¶ ACS 서비스 주소

* Assertion Consumer Service

¶ 서비스제공자 식별자

¶ 서명

¶ 인증방법(ID/PW, OTP 등)

등등

```
<saml:AuthnRequest
  xmlns:saml="urn:oasis:names:tc:SAML:2.0:protocol"
  xmlns:saml="urn:oasis:names:tc:SAML:2.0:assertion"
  ID="_bc6335d0970e40d7d40c161ca9e1adcf1d2d47c3d4"
  Version="2.0"
  IssueInstant="2022-11-14T08:17:21Z"
  Destination="https://saml.kafe.or.kr/simplesaml/saml2/idp/SSOService.php"
  AssertionConsumerServiceURL="https://webinar.kafe.or.kr/simplesaml/module.php/saml/sp/saml2-accs.php/default-sp"
  ProtocolBinding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
  <saml:Issuer>https://webinar.kafe.or.kr/sp/simplesamlphp</saml:Issuer>
  <saml:NameIDPolicy
    Format="urn:oasis:names:tc:SAML:2.0:nameid-format:transient"
    AllowCreate="true"/>
  <saml:Scoping>
    <saml:RequesterID>https://webinar.kafe.or.kr/sp/python</saml:RequesterID>
  </saml:Scoping>
</saml:AuthnRequest>
```


SAML Response with Assertion

인증요청에 대한 응답으로 아이디제공자가 전송

메시지 내용

¶ 발행자(Issuer)

¶ 서명(Signature)

- * digest(간추림)를 개인키로 암호화

¶ X.509 인증서

- * 서명검증 및 복호화

¶ 인증정보

- * 누가, 언제, 어떤 서비스제공자를 위해
어떤 인증방식(예, 비밀번호)으로 로그인했고
- * 메시지가 언제까지 유효한지를 기록

¶ 속성값

<참고> SAML에서 서명과 검증은 **매우** 중요한 보안요소입니다.

```
<saml:ArtifactResponse xmlns:saml="urn:oasis:names:tc:SAML:2.0:protocol"
  ID="s2d9926a42ce0f17629c6af30a6dd8a15fa7409415" InResponseTo="RkN2Yn1EM"
  Version="2.0" IssueInstant="2007-01-02T20:48:35Z">
  <saml:Issuer xmlns:saml="urn:oasis:names:tc:SAML:2.0:assertion">
    idp.ssocircle.com
  </saml:Issuer>
  <saml:Status xmlns:saml="urn:oasis:names:tc:SAML:2.0:protocol">
    <saml:StatusCode xmlns:saml="urn:oasis:names:tc:SAML:2.0:protocol"
      Value="urn:oasis:names:tc:SAML:2.0:status:Success">
    </saml:StatusCode>
  </saml:Status>
  <saml:Response xmlns:saml="urn:oasis:names:tc:SAML:2.0:protocol"
    ID="s276a3300f0e2b3d7f67a800d332156f0fdb99c5d0"
    InResponseTo="NKRDzVK7e" Version="2.0" IssueInstant="2007-01-02T20:48:35Z">
    <saml:Issuer xmlns:saml="urn:oasis:names:tc:SAML:2.0:assertion">
      idp.ssocircle.com
    </saml:Issuer>
    <saml:Status xmlns:saml="urn:oasis:names:tc:SAML:2.0:protocol">
      <saml:StatusCode xmlns:saml="urn:oasis:names:tc:SAML:2.0:protocol"
        Value="urn:oasis:names:tc:SAML:2.0:status:Success">
      </saml:StatusCode>
    </saml:Status>
    <saml:Assertion xmlns:saml="urn:oasis:names:tc:SAML:2.0:assertion" Version="2.0"
      ID="s25d1bbb23edi3c6da325a627637c6dc5d9e7f13a9" IssueInstant="2007-01-02T20:48:35Z">
      <saml:Issuer>
        idp.ssocircle.com
      </saml:Issuer>
      <saml:Subject>
        <saml:NameID NameQualifier="idp.ssocircle.com" Format="urn:oasis:names:tc:SAML:2.0:nameid-format:persistent">
          amv90yvHQrEW2rmaRViMpWX4qyDA
        </saml:NameID>
        <saml:SubjectConfirmation Method="urn:oasis:names:tc:SAML:2.0:cm:bearer">
          <saml:SubjectConfirmationData NotOnOrAfter="2007-01-02T20:58:35Z" InResponseTo="NKRDzVK7e"
            Recipient="http://cgi.cohos.de:80/cgi-bin/xmid"></saml:SubjectConfirmationData>
        </saml:SubjectConfirmation>
      </saml:Subject>
      <saml:Conditions NotBefore="2007-01-02T20:48:35Z" NotOnOrAfter="2007-01-02T20:58:35Z">
        <saml:AudienceRestriction>
          <saml:Audience>
            http://cgi.cohos.de:80/cgi-bin/xmid?c=B
          </saml:Audience>
        </saml:AudienceRestriction>
      </saml:Conditions>
      <saml:AuthnStatement AuthnInstant="2007-01-02T20:48:35Z" SessionIndex="s24bfc21323ee9c117bf5769a074be1ff177262701">
        <saml:AuthnContext>
          <saml:AuthnContextClassRef>
            urn:oasis:names:tc:SAML:2.0:ac:classes:PasswordProtectedTransport
          </saml:AuthnContextClassRef>
        </saml:AuthnContext>
      </saml:AuthnStatement>
    </saml:Assertion>
  </saml:Response>
```

Digital Signature




Image Source: <https://www.identityfusion.com/>

①

```
<saml:Assertion
  xmlns:xs="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  ID="_4ee1121c24771a9cf31ef208923f12f5d9e24d8722"
  Version="2.0"
  IssueInstant="2022-11-14T08:17:35Z">
  <saml:Issuer>https://saml.kafe.or.kr/idp/simpleSamlPhp</saml:Issuer>
  <ds:Signature
    xmlns:ds="http://www.w3.org/2000/09/xmldsig#"
    <ds:SignedInfo>
      <ds:CanonicalizationMethod
        Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
      <ds:SignatureMethod
        Algorithm="http://www.w3.org/2001/04/xmldsig-more#rsa-sha256" />
      <ds:Reference
        URI="#_4ee1121c24771a9cf31ef208923f12f5d9e24d8722">
        <ds:Transforms>
          <ds:Transform
            Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-signature" />
          <ds:Transform
            Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
        </ds:Transforms>
        <ds:DigestMethod
          Algorithm="http://www.w3.org/2001/04/xmenc#sha256" />
        <ds:DigestValue>
          whUztIpkv4Uo9p3kJbm3aVvYlX1biAyZLfWzYyJ6vK8=
        </ds:DigestValue>
      </ds:Reference>
    </ds:SignedInfo>
    <ds:SignatureValue>M3Hj+Vzab43p3JW1uU1H1aVZN1DF1bZn+U32CmbAUjCCVh4yJnMkvsz6681GiOrUA+NTL08N24oa1VjnpTsBUBckhRw69UgdCf/V0S
      Zp0AYuR1USW1IQw==
    </ds:SignatureValue>
    <ds:KeyInfo>
      <ds:X509Data>
        <ds:X509Certificate>MIIDOTCCArmGAWIBAgIJAOHgLPVea1i4MA0GCSqGSIb3Q0EBCwUAMH8xCzAJBgNVBAYTaktSMRAwQgYDVQQHDAAdEVWVqZjVz
        </ds:X509Data>
      </ds:KeyInfo>
    </ds:Signature>
  </ds:Signature>
  <saml:Subject>
    <saml:NameID
      SPNameQualifier="https://webinar.kafe.or.kr/sp/simpleSamlPhp"
      Format="urn:oasis:names:tc:SAML:2.0:nameid-format:transient">_9c25d611ebb697df5b96798d37f029a347b7586685
    </saml:NameID>
    <saml:SubjectConfirmation
      Method="urn:oasis:names:tc:SAML:2.0:cm:bearer">
      <saml:SubjectConfirmationData
```

②

Attributes in SAML Assertion

Assertion에 속성(Attributes) 포함


Friendly name/OID 형식 표기

¶ Friendly name

(예): cn/commonName, sn/surName,

¶ OID(Object Identifier)

(예): URN:OID:2.5.4.3



displayName


- SAML Name: urn:oid:2.16.840.1.113730.3.1.241
- LDAP source attribute: suDisplayName
- Example: Prof. John Doe

```
<saml:AttributeStatement>
  <saml:Attribute
    Name="urn:oid:2.16.840.1.113730.3.1.241"
    NameFormat="urn:oasis:names:tc:SAML:2.0:attrname-format:uri">
    <saml:AttributeValue
      xsi:type="xs:string">Jinyong JO
    </saml:AttributeValue>
  </saml:Attribute>
  <saml:Attribute
    Name="urn:oid:0.9.2342.19200300.100.1.3"
    NameFormat="urn:oasis:names:tc:SAML:2.0:attrname-format:uri">
    <saml:AttributeValue
      xsi:type="xs:string">jinyong.jo@gmail.com
    </saml:AttributeValue>
  </saml:Attribute>
  <saml:Attribute
    Name="urn:oid:1.3.6.1.4.1.5923.1.1.1"
    NameFormat="urn:oasis:names:tc:SAML:2.0:attrname-format:uri">
    <saml:AttributeValue
      xsi:type="xs:string">staff
    </saml:AttributeValue>
    <saml:AttributeValue
      xsi:type="xs:string">member
    </saml:AttributeValue>
  </saml:Attribute>
  <saml:Attribute
    Name="urn:oid:2.5.4.10"
    NameFormat="urn:oasis:names:tc:SAML:2.0:attrname-format:uri">
    <saml:AttributeValue
      xsi:type="xs:string">KISTI
    </saml:AttributeValue>
  </saml:Attribute>
  <saml:Attribute
    Name="urn:oid:1.3.6.1.4.1.5923.1.1.1.6"
    NameFormat="urn:oasis:names:tc:SAML:2.0:attrname-format:uri">
    <saml:AttributeValue
      xsi:type="xs:string">jiny92@coren.or.kr
    </saml:AttributeValue>
  </saml:Attribute>
  <saml:Attribute
    Name="urn:oid:1.3.6.1.4.1.25178.1.2.9"
    NameFormat="urn:oasis:names:tc:SAML:2.0:attrname-format:uri">
    <saml:AttributeValue
      xsi:type="xs:string">coren.or.kr
    </saml:AttributeValue>
  </saml:Attribute>
  <saml:Attribute
    Name="urn:oid:1.3.6.1.4.1.5923.1.1.1.10"
    NameFormat="urn:oasis:names:tc:SAML:2.0:attrname-format:uri">
    <saml:NameID
      NameQualifier="https://coren-idp.kreonet.net/ldap/simplesamlphp"
      SPNameQualifier="https://filesender.kreonet.net/sp/simplesamlphp"
      Format="urn:oasis:names:tc:SAML:2.0:nameid-format:persistent">d74f17c949df30493dc8cf7171959c01716f1d03
    </saml:NameID>
    <saml:AttributeValue>
  </saml:AttributeValue>
  </saml:Attribute>
</saml:AttributeStatement>
```

Attributes provided

서비스제공자는 요구속성을 SP
메타데이터에 기록

1. 개체식별자(entityID) 및 요구속성 확인



2. 요구속성 제공

```

<?xml version="1.0" encoding="UTF-8"?>
<md:EntityDescriptor xmlns="urn:oasis:names:tc:SAML:2.0:metadata" xmlns:md="urn:oasis:names:tc:SAML:2.0:metadata"
xmlns:ds="http://www.w3.org/2000/09/xmldsig#" xmlns:saml="urn:oasis:names:tc:SAML:2.0:assertion"
xmlns:shibmd="urn:mace:shibboleth:metadata:1.0" xmlns:mdui="urn:oasis:names:tc:SAML:2.0:ui"
xmlns:mdattr="urn:oasis:names:tc:SAML:2.0:attribute" xmlns:mdrpi="urn:oasis:names:tc:SAML:2.0:profile:idp-discovery-protocol"
xmlns:mdinit="urn:oasis:names:tc:SAML:2.0:profile:initialization" xmlns:xi="http://www.w3.org/2001/XInclude"
entityID="https://snu.bookcube.biz/sp/shibboleth">
  <md:Extensions>
    <mdrpi:RegistrationInfo registrationAuthority="http://kaf.kreonet.net" registrationID="1" />
  </md:Extensions>
  ...
  <md:AttributeConsumingService index="0">
    <md:ServiceName xml:lang="en">Bookcube for Seoul National University</md:ServiceName>
    <md:ServiceDescription xml:lang="en">It is a service that allows you to use e-books online. Users can use it to search for books and borrow them online.</md:ServiceDescription>
    <md:RequestedAttribute FriendlyName="eduPersonPrincipalName" Name="urn:oid:1.3.6.1.4.1.5923.1.1.1.6" NameFormat="urn:oasis:names:tc:SAML:2.0:attr-format:uri" />
    <md:RequestedAttribute FriendlyName="eduPersonAffiliation" Name="urn:oid:1.3.6.1.4.1.5923.1.1.1.1" NameFormat="urn:oasis:names:tc:SAML:2.0:attr-format:uri" />
    <md:RequestedAttribute FriendlyName="email" Name="urn:oid:0.9.2342.19200300.100.1.3" NameFormat="urn:oasis:names:tc:SAML:2.0:attr-format:uri" />
    <md:RequestedAttribute FriendlyName="displayName" Name="urn:oid:2.16.840.1.113730.3.1.241" NameFormat="urn:oasis:names:tc:SAML:2.0:attr-format:uri" />
  </md:AttributeConsumingService>
  ...
</md:EntityDescriptor>
  
```

SAML SP Metadata

Attributes 활용

응용서비스가 사용자 권한부여에 사용

예시

¶ kisti.re.kr에 소속된 학생만 서비스 이용을 허용하라!

<참고>

urn:oid:1.3.6.1.4.1.5923.1.1.1.9 ==
eduPersonScopedAffiliation

```
<saml:Attribute  
  Name="urn:oid:1.3.6.1.4.1.5923.1.1.1.9"  
  NameFormat="urn:oasis:names:tc:SAML:2.0:attrname-  
format:basic">  
  <saml:AttributeValue  
    xsi:type="xs:string">student@kisti.re.kr  
  </saml:AttributeValue>  
</saml:Attribute>
```

SAML Assertion 일부

서비스제공자 != 응용서비스

실습 #1

SP 메타데이터의 내용 확인

¶ 다운로드 받은 파일을 notepad++로 읽어오기

<https://testssp.kreonet.net/simplesaml/module.php/saml/sp/metadata.php/default-sp>

URL은 edu.kafe.or.kr를 참조

실습 #2

Chrome Plugin으로 SAML 메시지 내용 확인하기 ¶ AuthnRequest/Response 메시지

① [검증용 아이디제공자] <https://testidp.kreonet.net>로 이동

② 사용자 등록 메뉴에서 계정 생성

* 개인정보는 입력하지 마세요! 계정은 24시간 이후에 자동삭제 됩니다.




③ [검증용 서비스제공자] <https://testssp.kreonet.net>으로 이동

④ 로그인 검증 메뉴로 이동



⑤ Chrome 브라우저에서 F12 키 입력

* 우측 그림 참조



URL은 edu.kafe.or.kr를 참조

실습 #2 (계속)

⑥ [검증용 서비스제공자] 로그인버튼 클릭

⑦ KAFE test-idp를 선택

⑧ SAML Request 메시지 확인

⑨ 검증용 아이디제공자에서 만든 사용자 계정으로 로그인

⑩ SAML Response 메시지 확인

The screenshot shows a two-step login process. The top section, titled 'Select an AuthnContextRef type', has a dropdown menu with 'urn:oasis:names:tc:SAML:2.0:ac:classes:Password' selected and a blue 'LOGIN' button. The bottom section has a dropdown menu with 'KAFE Test-IdP' selected, a 'Select' button, and a checkbox labeled 'Remember my choice' which is currently unchecked.


URL은 edu.kafe.or.kr를 참조

[참고] Identity federation



Identity federation

Trust AA framework for multiple domains



An identity federation (or just federation) is **a collection of organizations that agree to interoperate under a certain rule set.**

: Trust framework의 준용에 동의한 조직의 집합

Federated Identity Management


Benefits

- Enables user to work together across domains
- Simplifies identity and access management
- Admins avoid common problems managing multi-domain access
- Help organizations save money and maintain control
- Eliminates barriers to resources and facilitates collaboration
- Eases data management, privacy and compliance


Drawbacks

- Upfront costs modifying existing systems and applications
- Creating policies adhering to security requirements for all users, which can be:
 - complicated
 - time-consuming
- Can become complicated to maintain as a company joins more federations
- Possibly a huge time commitment

How IDF simplifies things




Federation Architecture




Full mesh

Hybrid = Full mesh + Hub-and-spoke



Hub-and-spoke

Login with home institutions



Part II . 아이디어제공자의 구축



공개소스 SAML 소프트웨어

분류	Shibboleth	simpleSAMLphp
인증 플로우	비밀번호, X.509, SPNEGO/Kerberos, IP Address, etc	비밀번호(SQL/LDAP/Radius), X.509, Social media
표준지원	SAML 1.1/2.0, X.509, Kerberos, LDAP, SQL	SAML 1.1/2.0, OpenID, Oauth 2.0, Kerberos, VOOT, SQL, LDAP, RADIUS
구현 언어	Java(Spring) for IdP, Apache daemon for SP	PHP for IdP and SP
고가용성(HA) 지원	Yes	Yes (다수의 memcached를 통해 가능)
License	GNU GPL v2.0	GNU LGPL v2.1
지원	Shibboleth 컨소시엄	사용자 커뮤니티


아이디제공자의 구축

¶ 아이디제공자(IdP)

- * KAFE installer 이용
- * NTP 시간동기화 및 TLS 통신 필수
- * Apache 웹 서버에서 동작

¶ 데이터베이스

- * MySQL, Oracle, LDAP, AD, Tiberio, MSSQL, RESTful API, 등등



Why NTP?

¶ SAML response message

```
<saml:Conditions
  NotBefore="2022-11-21T02:14:44Z"
  NotOnOrAfter="2022-11-21T02:20:14Z">
  <saml:AudienceRestriction>
    <saml:Audience>...</saml:Audience>
  </saml:AudienceRestriction>
</saml:Conditions>
<saml:AuthnStatement
  AuthnInstant="2022-11-21T02:02:26Z"
  SessionNotOnOrAfter="2022-11-21T10:15:14Z"
  SessionIndex="_f70c5e79d90cb0bbcf19920844a36311940f280580">
  <saml:AuthnContext>
    <saml:AuthnContextClassRef>urn:oasis:names:tc:SAML:2.0:ac:classes:Password</saml:AuthnContextClassRef>
  </saml:AuthnContext>
</saml:AuthnStatement>
```

¶ SAML Metadata

```
<md:EntitiesDescriptor ID="kafe-20221128022233" Name="urn:mace:kisti.re.kr:kafe:testfed" validUntil="2022-11-28T02:22:33Z"
  <md:Extensions>
    <mdrpi:PublicationInfo creationInstant="2022-11-21T02:22:33Z" publisher="http://kafe.kreonet.net"/>
  </md:Extensions>
  <!--
https://proxy.kreonet.net/sp/simplesamlphp
-->
  <md:EntityDescriptor entityID="https://proxy.kreonet.net/sp/simplesamlphp">
    <md:Extensions>
      <mdrpi:RegistrationInfo registrationAuthority="http://kafe.kreonet.net" registrationInstant="2015-11-10T08:32:00Z"/>
    </md:Extensions>
```

데이터베이스 연동

① 아이디제공자 서버에 데이터베이스(예, Oracle) 라이브러리 설치

I. <http://www.oracle.com>에서 Oracle instant client 다운로드: oracle instantclient basic, oracle instant client devel

II. Instant client 설치 rpm -ivh xxxx.rpm

III. <http://pecl.php.net/package/oci8> 에서 oci8 다운로드

※ oci8 버전은 php 버전에 의존성 있으므로 php 버전에 맞는 oci8버전을 다운로드

IV. oci8 설치

```
$ tar xvf oci8-1.4.9.tgz
$ cd oci8-1.4.9
$ phpize
$ ./configure --with-oci8=shared,instantclient,/usr/lib/oracle/11.2/client64/lib
$ ln -s /usr/include/oracle/11.2/client64/ /usr/lib/oracle/11.2/client64/lib/include
$ make all install
```

V. php 연동: echo 'extension=oci8.so' > /etc/php.d/oci8.ini; service httpd restart

데이터베이스 연동(계속)

② 검증용 PHP 코드 작성

```
<?php
$user_id = "USER_ID";
$user_pw = "USER_PW";
$tns =
"(DESCRIPTION=(ADDRESS_LIST=(LOAD_BALANCE=ON)(FAILOVER=ON)(ADDRESS=(PROTOCOL=TCP)(HOST=192.168.10.10)(PORT=5055))(ADDRESS=(PROTOCOL=TCP)(HOST=192.168.10.11)(PORT=5505)))(CONNECT_DATA=(SERVICE_NAME=HELLO_WORLD)))";
$conn = oci_connect("DB_ID", "DB_PW", $tns, 'AL32UTF8 ');
if(!$conn){
    $e = oci_error();
    var_dump($e);
}else echo "success";

$query = "SELECT NAME, EMAIL, AFFLI FROM TABLE(ORACLE_FUNC('$user_id', '$user_pw' ))";
$stmt = oci_parse($conn, $query);
oci_execute($stmt);
if(!$row = oci_fetch_assoc($stmt)){
    $e = oci_error();
    var_dump($e);
}
var_dump($row);
oci_free_statement($stmt);
oci_close($conn);
?>
```

데이터베이스 연동(계속)

③ simpleSAMLphp 소스코드 수정

* /var에 simplesamlphp가 설치된 경우

```
[root@localhost ~]# nano /var/simplesamlphp/modules/kafe/lib/Auth/Source/CoreAuth.php
```

* protected function login(\$username, \$password) 함수 수정

☞ 아래 그림의 예시 임

```
protected function login($username, $password) {  
    $db = new PDO($this->dsn, $this->username, $this->password);  
    $db->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);  
    $db->exec("SET NAMES 'utf8'");  
  
    $st = $db->prepare("SELECT username, password, name, email, affi from ex_users where username = '$username'");  
    if(!$st->execute()){  
        throw new Exception('Failed to Query database for the user');  
    }  
}
```

데이터베이스 연결부

데이터베이스 질의부

데이터베이스 연동(계속)

② simpleSAMLphp 소스코드 수정(contd.)

* 질의(Query) 결과를 SAML attributes로 변환

```
$attributes = array(
    'uid' => array($username),
    'displayName' => array($row['name']),
    'cn' => array($row['name']),
    'sn' => $sn,
    'givenName' => $givenname,
    'mail' => array($row['email']),
    'eduPersonAffiliation' => $this->eAffiliation,
    'eduPersonPrincipalName' => $epName,
    'eduPersonScopedAffiliation' => $epsAffiliation,
    'organizationName' => array('YOUR ORG FULL NAME'),
    'schacHomeOrganization' => array('yourorg.ac.kr'),
    // for future use
    'eduPersonEntitlement' => array('urn:mace:dir:entitlement:common-lib-terms'),
);
```

* 이용 가능한 속성명 확인

```
[root@localhost ~]# nano /var/simplesamlphp/attributemap/name2oid.php
```

```
$attributemap = [
    'aRecord' => 'urn:oid:0.9.2342.19200300.100.1.26',
    'aliasedEntryName' => 'urn:oid:2.5.4.1',
    'aliasedObjectName' => 'urn:oid:2.5.4.1',
    'associatedDomain' => 'urn:oid:0.9.2342.19200300.100.1.37',
    'associatedName' => 'urn:oid:0.9.2342.19200300.100.1.38',
    'audio' => 'urn:oid:0.9.2342.19200300.100.1.55',
    'authorityRevocationList' => 'urn:oid:2.5.4.38',
```

[참고] Inter-Federation



Federations Map

¶ 아이디 페더레이션의 국가 간 확장



국외 응용서비스 이용

¶ 국제 신원연합 eduGAIN을 통해 연합 메타데이터 교환

- * 개인정보처리방침을 제공하는 아이디제공자와 서비스제공자만 수용
- * 여과된 eduGAIN 메타데이터 배포 주소(서비스제공자 확인 가능)

<https://fedinfo.kreonet.net/signedmetadata/federation/KAFE-eduGAIN/eduGAIN-SP.xml>

¶ 조건

- * eduGAIN 가입(KAFE 가입 시 선택)
- * 아이디제공자의 경우, SIRTFI(보안사고 대응프레임워크) 및 Research & scholarship category(개인정보최소사용) 준수

Federations in eduGAIN ?		Entities in eduGAIN ?	
Participants	80	All entities	8801
Voting-only Members	1	IdPs	5185
Candidates	5	SPs	3631
		Standalone AAs	2

```

<mdattr:EntityAttributes>
  <saml:Attribute Name="http://macedir.org/entity-category-support" NameFormat="urn:oasis:names:tc:SAML:2.0:attrname-format:uri">
    <saml:AttributeValue>http://refeds.org/category/research-and-scholarship</saml:AttributeValue>
  </saml:Attribute>
  <saml:Attribute Name="urn:oasis:names:tc:SAML:attribute:assurance-certification" NameFormat="urn:oasis:names:tc:SAML:2.0:attrname-format:uri">
    <saml:AttributeValue>https://refeds.org/sirtfi</saml:AttributeValue>
  </saml:Attribute>
</mdattr:EntityAttributes>

```

SIRTFI 중 TLP 규정

¶ TLP(Traffic Light Protocol)

- * 민감정보의 공유범위를 지정
- * 참조: <https://www.cisa.gov/tlp>

181.1.253.234, IPV4ADDR, ,IP_WATCHLIST, C2, 12/28/2017 00:10:25Z, TLP:WHITE, According to DHS and FBI analysis, this IP address is compromised infrastructure. This IP is geolocated in Argentina.

 TLP: RED Not For Disclosure This information cannot be disseminated to third parties unless the sender permits it Only participating groups can have access to it. 예) 허락된 사용자	 TLP: AMBER Limited Disclosure This information can be shared with participants of an organization or some members of a community Additional restrictions can be made. 예) 특정 학교의 전산소
 TLP: GREEN Community-Wide Disclosure This information can be shared with everyone in a particular community However, it cannot be published publicly on the Internet. 예) 모든 학교의 전산소/공개불가	 TLP: WHITE Unlimited Disclosure This information can be shared publicly with everyone However, the laws of Copyright still need to be applied 예) 모두

Image Source: <https://cyberhoot.com/cybrary/traffic-light-protocol/>

Part III. MFA



Multi-Factor Authentication

MFA(Multi-Factor Authentication)

- ¶ Something you know(지식)
eg., Password or PIN
- ¶ Something you have(소유)
eg., token(smartphone, key, smart card)
- ¶ Something you are(생체)
eg., 지문, 홍채, 안면인식



Step 1
Username and
password entered



Step 2
Token or PIN entered



Step 3
Fingerprint or other
biometric verified

Image Source: <https://www.rsa.com/multi-factor-authentication/what-is-mfa/>

Why MFA?


- ¶ 150억 개의 크리덴셜(예, 아이디/비밀번호 등)이 유출
- ¶ Google의 경우, 주 당 250,000개의 웹 로그인에 탈취
- ¶ 해킹 관련 데이터 유출의 약 80%가 탈취된/취약한 비밀번호로 인한

GDPR and NIST guidelines →

Strong authentication

Types of MFA

¶ Secure?



Source: GAO | GAO-19-138

PIV(Personal Identity Verification) smart card


IVR: Interactive Voice Response

Type of MFA		NIST-Compliant	Phishing-Resistant	% Targeted Phishing Attacks Resisted ¹	Notes
Other	Last Sign-In Location	No	No	0%	
	Knowledge Questions	No	No	40%	
	Email OTP	No	No	75%	
	Desktop OTP	Yes	No	85%	
Mobile Authenticators	SMS OTP	No	No	75%	Lower cost and complexity, but mobile devices not always allowed or available
	IVR OTP	No	No	75%	
	App OTP (i.e. Google Authenticator)	Yes	No	80%	
	Push Notification	Yes	No	90%	
	FIDO2/WebAuthn mobile token	Yes	Yes	100%	
Hardware Authenticators	OTP hardware token	Yes	No	100%	Higher cost and complexity, but sometimes required
	FIDO2/WebAuthn security key	Yes	Yes	100%	
	PIV smart card	Yes	Yes	100%	
	PIV-derived authenticator	Yes	Yes	100%	

Image Source:
<https://surepassid.com/blog/2023/01/11/types-of-mfa-compared>

Authenticator Assurance Level

¶ NIST AAL



예) 소프트웨어 인증서, 비밀번호

예) 스마트폰 OTP, 하드웨어 OTP 토큰

예) 스마트카드, FIDO2 키

Image Source: <https://www.yubico.com/>


When apply?

¶ FIPS 201 (Federal Information Processing Standard Publication 201) - 3: 개인정보검증 사양서(연방정부 관련자)

불편함, 고통 또는 명예나 평판에 대한 손해
 재정적 손실 또는 연방기관의 법적 책임
 연방기관 프로그램이나 공익에 대한 피해
 민감 정보의 무단 공개
 개인의 안전
 민사적 또는 형사적 법률 위반




When apply? (Contd.)



[참고] How TOTP works?

¶ TOTP: Time-based One-Time Password RFC 6238



기존시간(Unix time)

현재시간(Unix time)

비밀키(Secret key)

$$TOTP_v = Truncate(HMAC_H(K, \frac{(T_c - T_o)}{T_x}))$$

갱신간격(Time step)


HMAC: Hash-based Message Authentication Code

Federation 환경에서 MFA 실행 주체

¶ 아이디제공자

서비스제공자 제공 시,
사용자는 다수의 토큰을 보유해야 함

서비스제공자에서
MFA의 실행여부 확인 방법?




REFEDS MFA Profile

¶ 단체표준

¶ MFA의 실행 요청과 실행 확인

¶ MFA의 보장등급(AAL)은 지정하지 않음



REFEDS MFA Profile (Contd.)

¶ SAML Request & Response messages

MFA syntax: <https://refeds.org/profile/mfa>

MFA request message

```

1 <samlp:AuthnRequest
2   Version="2.0"
3   IssueInstant="2023-06-09T06:37:11Z">
4   <saml:Issuer>https://saml.kafe.or.kr/sp/simplesamlphp</saml:Issuer>
5   <samlp:RequestedAuthnContext>
6     <saml:AuthnContextClassRef>
7       https://refeds.org/profile/mfa
8     </saml:AuthnContextClassRef>
9   </samlp:RequestedAuthnContext>
10  <samlp:Scoping>
11    <samlp:RequesterID>https://oidc.kafe.or.kr/Saml2/sp</samlp:RequesterID>
12  </samlp:Scoping>
13 </samlp:AuthnRequest>

```

MFA response message

```

1 <samlp:Response
2   Version="2.0"
3   IssueInstant="2023-06-09T06:37:40Z">
4   <saml:Issuer>
5     https://saml.kafe.or.kr/idp/simplesamlphp
6   </saml:Issuer>
7   <samlp>Status>
8     <samlp:StatusCode
9       Value="urn:oasis:names:tc:SAML:2.0:status:Success"/>
10    </samlp:StatusCode>
11   <saml:Assertion>
12     <saml:AuthnStatement>
13       <saml:AuthnContext>
14         <saml:AuthnContextClassRef>
15           https://refeds.org/profile/mfa
16         </saml:AuthnContextClassRef>
17         <saml:AuthenticatingAuthority>
18           https://coreen-idp.kreonet.net/idp/simplesamlphp
19         </saml:AuthenticatingAuthority>
20       </saml:AuthnContext>
21     </saml:AuthnStatement>
22   </saml:Assertion>
23 </samlp:Response>

```

실습 #3

MFA Request 확인

- ① 스마트폰에 Google authenticator 설치
- ② Chrome 브라우저를 이용해 <https://console.console-neuron.ksc.re.kr/> 으로 이동
- ③ F12 클릭 후, SAML 메시지 캡처
- ④ 소속기관 사용자계정으로 로그인



Please enter the one-time password.

Next

- ⑤ 최초 로그인 시 QR code 스캔
- ⑥ OTP 입력

URL은 edu.kafe.or.kr를 참조

실습 #3 (Contd.)

MFA Response 확인

⑦ SAML response 메시지 확인

Korean Access Federation

<https://www.kafe.or.kr/>
support@kafe.or.kr